

## Section 1 - Identification of Chemical Product and Company

RustStop Pty Ltd  
1 Allen Street  
Loganholme QLD

Phone: 1300 710 443

Fax: 07 3398 3235

**Substance:** Hydrocarbon Solvent Solution  
**Trade Name:** RustStop RX100  
**Product Use:** Corrosion Inhibitor  
**Creation Date:** April, 2010  
**Revision Date:** April, 2010

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of NOHSC Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R11, R38, R62, R65, R67, R48/20, R51/53. Highly flammable. Irritating to skin. Possible risk of impaired fertility. Harmful: May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment.

**Safety Phrases:** S2, S16, S23, S29, S33, S36, S38, S46, S61, S62, S24/25. Keep out of reach of children. Keep away from sources of ignition - No smoking. Do not breathe vapours or mists. Do not empty into drains. Take precautionary measures against static discharges. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If swallowed, contact a doctor or Poisons Information Centre immediately and show this container or label. Avoid release to the environment. Refer to special instructions/Safety Data Sheets. If swallowed, do not induce vomiting: seek medical advice immediately and show this MSDS. Avoid contact with skin and eyes.

**SUSDP Classification:** S5

**ADG Classification:** Class 3 (FLAMMABLE LIQUID, N.O.S.)

**UN Number:** 1268

## Emergency Overview

**Physical Description & Colour:** Light amber liquid.

**Odour:** Characteristic solvent odour.

**Major Health Hazards:** Harmful if inhaled, skin irritant, possible risk of impaired fertility, if aspirated, may cause lung damage.

## Potential Health Effects

### Inhalation

**Short Term Exposure:** Available data shows that this product is harmful, but symptoms are not available. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term inhalation.

### Skin Contact:

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short Term Exposure:** This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

## MATERIAL SAFETY DATA SHEET

**Carcinogen Status:**

**NOHSC:** No significant ingredient is classified as carcinogenic by NOHSC.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Ethyl Benzene is classed 2b IARC - possibly carcinogenic to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

### Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Petroleum spirit	64742-89-8*	<50	not set	not set
Hexane	110-54-3	<5	72	not set
Ethyl benzene	100-41-4	<5	434	543
Proprietary agents deemed not hazardous		to 100		

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

**General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

### Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Preferred extinguishing media are carbon dioxide, dry chemical, foam. Foam is the preferred medium for large fires. Ensure that no spillage enters drains or water courses.

**Fire Fighting:** Immediately evacuate the area of unnecessary personnel.

**Flash point:** (Abel) -10°C

**Upper Flammability Limit:** 7.5%

**Lower Flammability Limit:** 1%

**Autoignition temperature:** 280°C

**Flammability Class:** Flammable

## MATERIAL SAFETY DATA SHEET

## Section 6 - Accidental Release Measures

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include PVC, Nitrile, neoprene. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Any electrical equipment should be non-sparking. Any equipment capable of building an electrostatic charge should be electrically grounded. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Can be slippery on floors, especially when wet. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
hexane	72	not set
Ethyl benzene	434	543

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: PVC, nitrile, neoprene.

**Respirator:** Where there is a risk of lengthy exposure to this product's vapours, we recommend that you use a respirator. It should be fitted with a type A cartridge, suitable for organic vapours. Otherwise, not normally necessary. Safety deluge showers should, if practical, be provided near to where this product is being used.

## MATERIAL SAFETY DATA SHEET

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Light amber liquid.
<b>Odour:</b>	Characteristic solvent odour.
<b>Boiling Point:</b>	Solvent Boils in the range 50-135°C at 100kPa
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	Hydrocarbon content.
<b>Vapour Pressure:</b>	Approx 35kPa at 20°C
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	0.7-0.8
<b>Water Solubility:</b>	Insoluble.
<b>pH:</b>	Not applicable.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water Distribution:</b>	No data
<b>Autoignition temp:</b>	280°C

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water, silica and other silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

**Toxicity:** A summary of white spirit type hydrocarbons can be found at

<http://www.inchem.org/documents/ehc/ehc/ehc187.htm>

Ingestion of white spirit has been reported to produce gastrointestinal irritation with pain, vomiting and diarrhoea.

Lesions of the mucous membranes in the oesophagus and the gastrointestinal tract followed the oral exposure.

Owing to its low viscosity and low surface tension, white spirit poses a risk of aspiration into the lungs following oral exposure. A few ml of solvent aspirated into the lungs are able to produce serious bronchopneumonia and 10-30ml may be fatal.

Prolonged dermal exposure to white spirit, e.g., resulting from wearing clothes that have been soaked or moistened by white spirit for hours, may produce irritation and dermatitis.

Single cases of acute toxicity to the kidney, liver and bone marrow have been reported following exposure to white spirit at high levels. However, owing to lack of details and the sporadic nature of the reportings, the relevance of these findings is unclear.

Inhalation of aliphatic hydrocarbon vapours seems to show little toxicity, however, this product appears to increase the risk of impaired fertility by inhalation exposure.

## Section 12 - Ecological Information

Toxic to aquatic organisms, may cause long-term adverse effects to the aquatic environment. This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

## Section 13 - Disposal Considerations

**Disposal:** There are many pieces of legislation covering waste disposal and they differ in each state and territory, so each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. The Hierarchy of Controls seems to be common - the user should investigate: Reduce, Reuse, and Recycle and only if all else fails should disposal be considered. Note that properties of a product may change in use, so that the following suggestions may not always be appropriate. The following may help you in properly addressing this matter for this product. This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

## MATERIAL SAFETY DATA SHEET

## Section 14 - Transport Information

**ADG Code:** 1268, FLAMMABLE LIQUID, N.O.S.

**Hazchem Code:** 3[Y]E

**Special Provisions:** SP109, SP185, SP274

**Dangerous Goods Class:** Class 3, Flammable liquids.

**Packaging Group:** II

**Packaging Method:** 3.8.3, RT1

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

## Section 15 - Regulatory Information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredients: Petroleum spirit, hexane, Ethyl benzene, (all are liquid hydrocarbons) are mentioned in the SUSDP.

## Section 16 - Other Information

**This MSDS contains only safety-related information. For other data see product literature.**

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>CAS Number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOHSC</b>	National Occupational Health and Safety Commission
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the NOHSC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]

## MATERIAL SAFETY DATA SHEET